


**Vertical Laminar
Flow Cabinet**
---Double Sides Type



LED Display
Microprocessor control system, LED display



UV Lamp
Emission of 253.7 nanometers for most efficient decontamination



Double Sides
Double sides work bench, operators can sit face to face

ADVANTAGE

1. With memory function in case of power-failure.
2. Double sides work bench, 2~4 operators can work together.

TECHNICAL PARAMETERS

Model	FLOWDU1000	FLOWDU1400
External Size (W*D*H)	1040*660*1770mm	1440*660*1770mm
Internal Size (W*D*H)	940*560*545mm	1340*560*545mm
Work Surface Height	750mm	
Display	LED Display	
Airflow Velocity	Average of 0.3~0.5m/s	
Material	Main Body: Cold-rolled steel with anti-bacteria powder coating Work Table: 304 stainless steel	
Pre-Filter	Polyester fiber, washable	
HEPA Filter	99.999% efficiency at 0.3µm	
Noise	<65dB	
Front Window	Manual, 5mm toughened glass, anti-UV	
Max Opening	310mm	
UV Lamp	18W*1	30W*1
	Emission of 253.7 nanometers	
LED Lamp	12W*1	16W*1
Consumption	350W	600W
Caster	Universal caster with leveling feet	
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz	
Standard Accessory	LED lamp, UV lamp*2, Base stand	
Optional Accessory	Electric height adjustable base stand	
Gross Weight	150kg	186kg
Package Size (W*D*H)	1190*890*1340mm	1590*890*1340mm